

# Deko Style X



# SGS

## TECHNICAL DATA

	Characteristics	Detection method	Detection result
	Specification	EN 427	1220x230mm
	Thickness in total	EN 428	7.0mm(5mm+2mmIXPE)
	Thickness of wear layers	EN 429	0.50mm
	Dimension Stability	EN 434	shrinkage $\leq$ 0.02%; curling $\leq$ 0.07mm
	Residual indentation	EN 432	0.01mm
	Color fastness to light	ISO 105 B02	$\geq$ 6
	Flexibility- 20 mm mandrel	EN 435	No cracks
	Chemical Resistance	EN 423	Class zero
	Castor chair	EN 425	No disturbance, no delamination
	Wear resistance	EN660	pass
	Reaction to Fire (and Smoke Production)	EN 13501-1	Bf1-S1
	Slip resistance		R10
	Product-Content Safety	EN685	23, 34, 43
	Product-Content Safety	REACH SVHC	Complies

**7.0 mm**  
Thickness



Size: 1220x230x7.0mm  
(5+2mm IXPE)  
Wearlayer: 0.5mm  
Per Box: 8pcs, 2.2448sqm

Email: [Info@dekofloors.co.nz](mailto:Info@dekofloors.co.nz)  
Website: [www.dekofloors.co.nz](http://www.dekofloors.co.nz)